



SW2782

The basic model of the Swivl robot for international.

| | | |
|--------|----------------------|--|
| System | In the box | Base, Marker, AC Charger, 3x Adapter grips, Audio cable, Micro USB cable and Manual |
| | Weight | 2.1lbs package. Base 1.1lbs. Marker 0.15lbs. |
| | Pan | 360 degree continuous with max 45 degree/sec and 0.1degree step increment size |
| | Tilt | 25 degree range with max 10 degree/sec and 0.1degree step increment size |
| | Tracking | 2-30 foot range of operation line of site |
| | Mobile compatibility | iOS and Android with app integration, Windows not supported |
| | Camera compatibility | Select controls to Canon and Nikon cameras |
| Marker | Size | 80mm x 30mm |
| | Remote controls | Record, Action, Right & Left |
| | Microphone | 2.4Ghz Purepath Wireless Digital Mic, 30 ft range |
| | Lavaliere microphone | 3.5mm audio input compatible |
| | Battery | Re-chargeable Lithium Polymer with estimated 4 hour run time (usage dependent) |
| Base | Size | 125mm x 65mm |
| | Audio | 3.5mm audio output to mobile device or camera |
| | Device Mounting | Any mobile device or device with protective case under 12mm thick or camera under 6 lbs (requires camera mount – SW5050) |
| | Battery | Re-chargeable Lithium with estimated 4 hour run time (usage dependent) |
| | Mobile charging | 1Amp via a standard USB connection to base |
| | I/O | USB, micro USB, 2.5mm Shutter, 3.5mm audio |
| | AC Adapter | 90-240V, International plugs. |